

MILLS TEST CERTIFICATE

Certificate Number 903995007
Customer Drillerco
Customer Order ref 1569
Invoice No BW/23600707
Reel No 951714/07

Date :17-08-2023



Owner ID : B5769, B5770, B5771, B5772, B5773, B5774, B5775, B5776, B5777, B5778, B5779, B5780, B5781, B5782, B5783, B5784, B5785, B5786, B5787, B5788, B5789, B5790, B5791, B5792, B5793, B5794, B6784, B6785, B6786, B6787, B6788, B6789, B6790, B6791, B6792, B6793, B6794, B6795, B6796, B6797, B6798, B6799, B6800, B6801, B6802, B6803, B6804, B6805, B6806, B6807, B6808, B6809, B6810, B6811, B6812, B6813, B6814, B6815, B6816, B6817, B5831, B5832, B5841, B5842

Manufacturer of the rope : **BRUNTON WOLF WIRE ROPES FZCO**

SPECIFICATION

Applied standard : API-9A:2011& BW Specification
Nominal Diameter of rope : 16.00 mm
Construction : 19X6
Strand construction : 12X6:6X6-1X6
Tensile grade of steel wire : 1960 N/mm²
Wire Finish/Material grade : UNGALV
Length of rope : 1000 mtr
Mass/unit length (appx) : 1.059 Kg/mtr
Type of core/Lay direction : WSC/RHO
Lubrication : A1
Minimum breaking force : 179.00 KN

RESULTS OF TEST & EXAMINATION

Measured dia. Off-tension : 16.30 mm
Measured lay. Off-tension : 101.00 mm
Measured breaking force : 189.70 kN

This is to certify that the above tests are in accordance with the specification.

Signature of

Competent person

